



# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 08/01/2018

Revision date: 02/05/2024

Supersedes: 02/06/2023

Version: 1.5

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Substance
Product name	: EUCALYPTOL USP OIL
CAS-No.	: 470-82-6
Product code	: 50-6107-01
Formula	: C10H18O
Synonyms	: 1,8-cineol / 1,8-cineole / 1,8-epoxy-para-menthane / 1,8-epoxy-p-menthane / 1,8-oxido-para-menthane / 1,8-oxido-p-menthane / 2-oxa-1,3,3-trimethylbicyclo(2.2.2)octane / 2-Oxabicyclo[2.2.2]octane, 1,3,3-trimethyl- / 8-epoxy-para-menthane / 8-epoxy-p-menthane / cajeputol / cineole / eucalyptol / eucalyptole / eucapur / eukalyptol / FEMA N° 2465 / limonene oxide / para-cineole / para-menthane, 1,8-epoxy- / p-cineole / p-menthane, 1,8-epoxy- / terpan / zedoary oil
BIG No	: 30348

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Odorant: component
------------------------------	----------------------

#### 1.3. Supplier

The Lebermuth Company  
4004 Technology Drive  
South Bend, IN 46628 - United States  
T 574-259-7000 - F 574-258-7450  
[info@lebermuth.com](mailto:info@lebermuth.com) - [www.lebermuth.com](http://www.lebermuth.com)

#### 1.4. Emergency telephone number

Emergency number	: CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300 CCN 13010
------------------	---

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 3	Flammable liquid and vapor
Serious eye damage/eye irritation Category 2B	Causes eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)	: Warning
Hazard statements (GHS US)	: Flammable liquid and vapor May cause an allergic skin reaction Causes eye irritation
Precautionary statements (GHS US)	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If on skin: Wash with plenty of water.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see supplemental first aid instruction on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use media other than water to extinguish.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Name	Product identifier	%	GHS US classification
EUCALYPTOL	(CAS-No.) 470-82-6	100	Flam. Liq. 3, H226 Eye Irrit. 2B, H320 Skin Sens. 1B, H317

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water. Take victim to a doctor if irritation persists. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth with water. Call Poison Information Centre ([www.big.be/antigif.html](http://www.big.be/antigif.html)). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : No effects known.

Symptoms/effects after skin contact : No effects known. May cause an allergic skin reaction.

Symptoms/effects after eye contact : No effects known.

Symptoms/effects after ingestion : No effects known.

Chronic symptoms : Skin rash/inflammation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (not alcohol-resistant). Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : DIRECT FIRE HAZARD: Flammable liquid and vapour. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD: May be ignited by sparks. Flammable liquid and vapor.
- Explosion hazard : DIRECT EXPLOSION HAZARD: Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD: May be ignited by sparks.
- Reactivity : Flammable liquid and vapor.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.
- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves (EN 374). Face shield (EN 166). Protective clothing (EN 14605 or EN 13034).
- Emergency procedures : Ventilate spillage area. Mark the danger area. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Wash contaminated clothes. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent spreading in sewers.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. Heating: dilute combustible gas/vapour with water curtain.
- Methods for cleaning up : Take up liquid spill into absorbent material. Take up liquid spill into inert absorbent material, e.g.: sand/earth. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Observe very strict hygiene - avoid contact. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: organic materials.
- Storage area : Meet the legal requirements. Store at room temperature. Store in a dry area. Keep container in a well-ventilated place. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### EUCALYPTOL (470-82-6)

No additional information available

##### EUCALYPTOL (470-82-6)

No additional information available

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Materials for protective clothing:

GIVE GOOD RESISTANCE: neoprene (chloroprene rubber). butyl rubber

##### Hand protection:

Gloves

##### Eye protection:

Face shield. Safety glasses

##### Skin and body protection:

Protective clothing

##### Respiratory protection:

High gas/vapour concentration: full face mask with filter type A

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: COLORLESS LIQUID
Odor	: AROMATIC CAMPHORACEOUS AROMA
Odor threshold	: No data available
pH	: No data available in the literature
Melting point	: -1.3 °C (OECD 102: Melting Point/Melting Range)
Freezing point	: No data available
Boiling point	: 177 °C (1013 hPa, OECD 103: Boiling Point)
Flash point	: 45 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 1.22 hPa (20 °C, OECD 104: Vapour Pressure)
Relative vapor density at 20°C	: 5.3 (Calculated)
Relative density	: 0.9235 (0.921 – 0.924)
Density	: 926 kg/m <sup>3</sup> (20 °C, OECD 109: Density of Liquids and Solids)
Molecular mass	: 154.3 g/mol
Solubility	: Insoluble. Water: 0.24 g/100ml
Partition coefficient n-octanol/water (Log Pow)	: 3.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Auto-ignition temperature	: 300 °C (DIN 51794: Self-ignition temperature, T3)
Decomposition temperature	: No data available in the literature
Viscosity, kinematic	: 2.1 mm <sup>2</sup> /s (40 °C, OECD 114: Viscosity of Liquids)
Viscosity, dynamic	: 3.16 mPa·s (20 °C, Calculated)
Explosion limits	: No data available
Explosive properties	: Not classified.
Oxidizing properties	: Not classified.

#### 9.2. Other information

VOC content	: 100 %
Refractive index	: 1.457 (1.455 – 1.46)
Other properties	: Gas/vapour heavier than air at 20°C. Slightly volatile.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (inhalation) : Not classified

EUCALYPTOL (470-82-6)	
LD50 oral rat	4500 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))
ATE US (oral)	2480 mg/kg body weight

EUCALYPTOL (470-82-6)	
LD50 oral rat	4500 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))
ATE US (oral)	2480 mg/kg body weight

Skin corrosion/irritation : Not classified  
pH: No data available in the literature

Serious eye damage/irritation : Causes eye irritation.  
pH: No data available in the literature

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

EUCALYPTOL (470-82-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other., Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3150 (90-Day Oral Toxicity in Non-rodents)

Aspiration hazard : Not classified

Viscosity, kinematic : 2.1 mm<sup>2</sup>/s (40 °C, OECD 114: Viscosity of Liquids)

Potential Adverse human health effects and symptoms : Practically non-toxic if swallowed (LD50 oral, rat > 2000 mg/kg). Not irritant to skin. Practically non-toxic in contact with skin (LD50 skin > 2000 mg/kg). Not irritant to eyes.

Symptoms/effects after inhalation : No effects known.

Symptoms/effects after skin contact : No effects known. May cause an allergic skin reaction.

Symptoms/effects after eye contact : No effects known.

Symptoms/effects after ingestion : No effects known.

Chronic symptoms : Skin rash/inflammation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.

Ecology - air : Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Photooxidation in the air. Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

Ecology - water : Slightly harmful to crustacea (Daphnia). Harmful to fishes. Groundwater pollutant. No inhibition of activated sludge. Slightly harmful to algae.

EUCALYPTOL (470-82-6)	
LC50 - Fish [1]	57 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EUCALYPTOL (470-82-6)	
LC50 - Fish [1]	57 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

### 12.2. Persistence and degradability

EUCALYPTOL (470-82-6)	
Persistence and degradability	Readily biodegradable in water.

EUCALYPTOL (470-82-6)	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

EUCALYPTOL (470-82-6)	
BCF - Other aquatic organisms [1]	112 l/kg (Literature study, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

EUCALYPTOL (470-82-6)	
BCF - Other aquatic organisms [1]	112 l/kg (Literature study, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

EUCALYPTOL (470-82-6)	
Surface tension	61.5 mN/m (20 °C, 1 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.33 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for adsorption in soil.

EUCALYPTOL (470-82-6)	
Surface tension	61.5 mN/m (20 °C, 1 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.33 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Do not discharge into drains or the environment. Dispose of at authorized waste collection point. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1197 Extracts, flavoring, liquid (Regulated for Bulk only), 3, III



# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No.(DOT)	: UN1197
Proper Shipping Name (DOT)	: Extracts, flavoring, liquid (Regulated for Bulk only)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.

### Transportation of Dangerous Goods

Transport document description (TDG)	: UN1197 EXTRACTS, FLAVOURING, LIQUID (Regulated for Bulk only), 3, III
UN-No. (TDG)	: UN1197
Proper Shipping Name (TDG)	: EXTRACTS, FLAVOURING, LIQUID
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group (TDG)	: III - Minor Danger
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

### Transport by sea

Transport document description (IMDG)	: UN 1197 EXTRACTS, LIQUID, 3, III
UN-No. (IMDG)	: 1197
Proper Shipping Name (IMDG)	: EXTRACTS, LIQUID
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

### Air transport

Transport document description (IATA)	: UN 1197 Extracts, liquid, 3, III
UN-No. (IATA)	: 1197
Proper Shipping Name (IATA)	: Extracts, liquid



# EUCALYPTOL USP OIL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : III - Low danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### EUCALYPTOL (470-82-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### EUCALYPTOL (470-82-6)

Listed on the Canadian DSL (Domestic Substances List)

##### EUCALYPTOL (470-82-6)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations

##### EUCALYPTOL (470-82-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

Revision date : 02/05/2024

Full text of H-phrases:

H226	Flammable liquid and vapor
H317	May cause an allergic skin reaction
H320	Causes eye irritation

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012) - Lebermuth

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*