

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 08/30/2018 Revision date: 04/09/2024 Supersedes: 04/24/2023 Version: 1.14

SECTION 1: Identification

Identification

Product form : Substance

Product name SPEARMINT FAR WEST NATIVE

CAS-No. 8008-79-5 Product code 50-6250-01

1.2. Recommended use and restrictions on use

1.3. **Supplier**

The Lebermuth Company 4004 Technology Drive South Bend, IN 46628 - United States T 574-259-7000 - F 574-258-7450 info@lebermuth.com - www.lebermuth.com

1.4. **Emergency telephone number**

Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300

CCN 13010

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 Combustible liquid Skin corrosion/irritation Category 2 Causes skin irritation

Skin sensitization, category 1B May cause an allergic skin reaction May cause damage to organs through prolonged or repeated exposure

Specific target organ toxicity (repeated exposure)

Category 2

Aspiration hazard Category 1 May be fatal if swallowed and enters airways

GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





GHS07

GHS08

Signal word (GHS US) : Danger

Hazard statements (GHS US) Combustible liquid

May be fatal if swallowed and enters airways

Causes skin irritation

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center or doctor.

If on skin: Wash with plenty of water.

Get medical advice/attention if you feel unwell.

Specific treatment (see supplemental first aid instruction on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

04/09/2024 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wash contaminated clothing before reuse.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS US classification
SPEARMINT OIL	(CAS-No.) 8008-79-5	100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Explosion hazard : No direct explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

04/09/2024 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment

: Wear recommended personal protective equipment.

Emergency procedures

Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Do not

breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures

Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep in a cool, well-ventilated place away from heat.

Storage conditions

: Store in a well-ventilated place. Keep cool. Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SPEARMINT OIL (8008-79-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

04/09/2024 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : COLORLESS TO PALE YELLOW LIQUID
Odor : CHARACTERISTIC MINTY ODOR

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available

Boiling point : 101 °C Atm. press.: 1013 hPa

Flash point : 64 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability : Not applicable. Vapor pressure : 60.36 Pa Temp.: 25 °C

Relative vapor density at 20°C : No data available
Relative density : 0.9271 (0.917 – 0.934)

Solubility : Insoluble.

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available

9.2. Other information

Refractive index : 1.489 (1.484 – 1.491)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

04/09/2024 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CEATI	AN 44.	Toyloglo	aigal in	formation
3E			uicai iii	

11.1. Information on	toxicological effects
----------------------	-----------------------

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

SPEARMINT OIL (8008-79-5)	
LD50 oral rat	≈ 5000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: other:
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
ATE US (oral)	4900 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

SPEARMINT OIL (8008-79-5)	
	0 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

04/09/2024 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Packing group (DOT)

Transport document description (DOT) : UN1197 Extracts, flavoring, liquid (Regulated for Bulk only), Comb Liq, III

UN-No.(DOT) : UN1197

Proper Shipping Name (DOT) : Extracts, flavoring, liquid

(Regulated for Bulk only)

III - Minor Danger

Class (DOT) : Comb Liq - Combustible liquid

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a

flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this

subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 1

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not regulated

μ .

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

SPEARMINT OIL (8008-79-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

04/09/2024 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

SPEARMINT OIL (8008-79-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations



This product can expose you to beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 04/09/2024

Full text of H-phrases:

ii text oi i i-piiiases.	
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012) - Lebermuth

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

04/09/2024 EN (English US) 7/7