

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.11

Issue date: 06/19/2018 Revision date: 04/23/2024 Supersedes: 05/17/2023

### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Product name : THYME ORGANIC OIL

CAS-No. : 8007-46-3 Product code : 50-6275-06

#### 1.2. Recommended use and restrictions on use

#### 1.3. Supplier

The Lebermuth Company 4004 Technology Drive South Bend, IN 46628 - United States T 574-259-7000 - F 574-258-7450 info@lebermuth.com - www.lebermuth.com

### 1.4. Emergency telephone number

Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300

CCN 13010

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 4 Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 1 Skin sensitization, Category 1

Reproductive toxicity Category 1
Aspiration hazard Category 1

Combustible liquid

Causes severe skin burns and eye damage

Causes serious eye damage May cause an allergic skin reaction

Suspected of damaging fertility or the unborn child May be fatal if swallowed and enters airways

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)







GHS05

GHS07

GHS08

Signal word (GHS US) : Danger

Hazard statements (GHS US) : Combustible liquid

May be fatal if swallowed and enters airways Causes severe skin burns and eye damage May cause an allergic skin reaction

Causes serious eye damage

Suspected of damaging fertility or the unborn child

Precautionary statements (GHS US) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center or doctor. If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

04/23/2024 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Immediately call a poison center or doctor.

Specific treatment (see supplemental first aid instruction on this label).

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

| Name      | Product identifier  | %   | GHS US classification   |
|-----------|---------------------|-----|---|
| THYME OIL | (CAS-No.) 8007-46-3 | 100 | Flam. Liq. 4, H227<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Repr. 2, H361<br>Asp. Tox. 1, H304 |

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns. Risk of lung edema.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Explosion hazard : No direct explosion hazard.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

04/23/2024 EN (English US) 2/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain

special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.

Packaging materials : Store always product in container of same material as original container.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### THYME OIL (8007-46-3)

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

04/23/2024 EN (English US) 3/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.







## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : YELLOW, YELLOW-ORANGE TO AMBER LIQUID

Odor : CHARACTERISTIC THYME ODOR

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available

Flash point : 64 °C

Relative evaporation rate (butyl acetate=1) : No data available
Flammability : Not applicable.

Vapor pressure : No data available
Relative vapor density at 20°C : No data available
Relative density : 0.9186 (0.888 – 0.927)

Solubility : Insoluble.

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic No data available **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties

9.2. Other information

Refractive index : 1.499 (1.486 – 1.51)

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

04/23/2024 EN (English US) 4/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ATE US (oral) 2500 mg/kg body weight

 Skin corrosion/irritation
 : Causes severe skin burns.

 Serious eye damage/irritation
 : Causes serious eye damage.

 Respiratory or skin sensitization
 : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns. Risk of lung edema.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations

04/23/2024 EN (English US) 5/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Disposal must be done according to official regulations. Sewage disposal recommendations Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description (DOT) : UN1760 Corrosive liquids, n.o.s. (Thyme Oil), 8, II

UN-No.(DOT) · LIN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

(Thyme Oil)

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** 

> passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

**Transportation of Dangerous Goods** 

Transport document description (TDG) : UN1760 CORROSIVE LIQUID, N.O.S. (Thyme Oil), 8, II

UN-No. (TDG) : UN1760

Proper Shipping Name (TDG) : CORROSIVE LIQUID. N.O.S. TDG Primary Hazard Classes : 8 - Class 8 - Corrosives

04/23/2024 EN (English US) 6/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (TDG)

: II - Medium Danger

**TDG Special Provisions** 

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not

required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.

Explosive Limit and Limited Quantity Index

Passenger Carrying Road Vehicle or Passenger : 1 L

Carrying Railway Vehicle Index

: 1L : 11

#### Transport by sea

Transport document description (IMDG) : UN 1760 CORROSIVE LIQUID, N.O.S. (Thyme Oil), 8, II

UN-No. (IMDG) : 1760

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S. Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 1 L

## Air transport

Transport document description (IATA) : UN 1760 Corrosive liquid, n.o.s. (Thyme Oil), 8, II

UN-No. (IATA) : 1760

Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

Class (IATA) : 8 - Corrosives

Packing group (IATA) : II - Medium danger

#### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

#### THYME OIL (8007-46-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

### CANADA

#### THYME OIL (8007-46-3)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

### **National regulations**

No additional information available

04/23/2024 EN (English US) 7/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 15.3. US State regulations



This product can expose you to methyl eugenol, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

This product can expose you to beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## **SECTION 16: Other information**

Revision date : 04/23/2024

### Full text of H-phrases:

| ווו נ | riext of n-pillases. |   |  |
|-------|----------------------|---|--|
|       | H227                 | Combustible liquid                                  |  |
|       | H304                 | May be fatal if swallowed and enters airways        |  |
|       | H314                 | Causes severe skin burns and eye damage             |  |
|       | H317                 | May cause an allergic skin reaction                 |  |
|       | H318                 | Causes serious eye damage                           |  |
|       | H361                 | Suspected of damaging fertility or the unborn child |  |

SDS US (GHS HazCom 2012) - Lebermuth

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

04/23/2024 EN (English US) 8/8