

1.1.

1.2.

1.3.

1.4.

2.1.

OIL, MONKEY FARTS*

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 04/02/2018 Revision date: 02/14/2024 Supersedes: 10/17/2022

Version: 1.6 **SECTION 1: Identification** Identification Product form : Mixture Product name : OIL, MONKEY FARTS* CAS-No. N/A Product code : 91-1006-65 Recommended use and restrictions on use **Supplier** The Lebermuth Company 4004 Technology Drive South Bend, IN 46628 - United States T 574-259-7000 - F 574-258-7450 info@lebermuth.com - www.lebermuth.com **Emergency telephone number** Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300 CCN 13010 SECTION 2: Hazard(s) identification **Classification of the substance or mixture GHS US classification** Flammable liquids Category 4 Combustible liquid Acute toxicity (inhalation vapor) Category 4 Harmful if inhaled Skin corrosion/irritation Category 2 Causes skin irritation Skin sensitization, Category 1 May cause an allergic skin reaction Specific target organ toxicity (repeated exposure) May cause damage to organs through prolonged or repeated exposure Category 2

2.2. GHS Label elements, including	precautionary statements
------------------------------------	--------------------------

GHS US labeling Hazard pictograms (GHS US) GHS07 GHS08 Signal word (GHS US) : Warning Combustible liquid Hazard statements (GHS US) Causes skin irritation May cause an allergic skin reaction Harmful if inhaled May cause damage to organs through prolonged or repeated exposure Precautionary statements (GHS US) Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Get medical advice/attention if you feel unwell. Specific treatment (see supplemental first aid instruction on this label). If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable 3.2. Mixtures

Name	Product identifier	%	GHS US classification
BENZYL BENZOATE	(CAS-No.) 120-51-4	10 – 25	Acute Tox. 4 (Oral), H302
D-LIMONENE	(CAS-No.) 5989-27-5	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304
LINALOOL	(CAS-No.) 78-70-6	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317
Allyl (3-methylbutoxy)acetate	(CAS-No.) 67634-00-8	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation), H330 Skin Irrit. 2, H315
ALLYL CYCLOHEXYLPROPIONATE	(CAS-No.) 2705-87-5	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Sens. 1, H317
ETHYL CAPROATE	(CAS-No.) 123-66-0	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315
ANISIC ALDEHYDE	(CAS-No.) 123-11-5	1 – 5	STOT RE 2, H373
VANILLIN	(CAS-No.) 121-33-5	1 – 5	Eye Irrit. 2A, H319
ETHYL BUTYRATE	(CAS-No.) 105-54-4	1 – 5	Flam. Liq. 3, H226 Eye Irrit. 2A, H319
COUMARIN	(CAS-No.) 91-64-5	1 – 5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Sens. 1B, H317
ALLYL HEXANOATE	(CAS-No.) 123-68-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:vapour), H331

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	 Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms and effe	cts (acute and delayed)
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
4.3. Immediate medical attention and sp	pecial treatment, if necessary
Treat symptomatically.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishing media			
Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.		
5.2. Specific hazards arising from the cher	nical		
Fire hazard :	Combustible liquid.		
Reactivity	The product is non-reactive under normal conditions of use, storage and transport.		
5.3. Special protective equipment and pre-	cautions for fire-fighters		
Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.		
SECTION 6: Accidental release measu	ires		
6.1. Personal precautions, protective equi	pment and emergency procedures		
6.1.1. For non-emergency personnel			
Emergency procedures :	Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.		
6.1.2. For emergency responders			
Protective equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Avoid release to the environment.			
6.3. Methods and material for containment	t and cleaning up		
Methods for cleaning up	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.		
Other information :	Dispose of materials or solid residues at an authorized site.		
6.4. Reference to other sections			
For further information refer to section 13.			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.		
Hygiene measures :	Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including			
Storage conditions :	Store in a well-ventilated place. Keep cool.		
SECTION 8: Exposure controls/persor	nal protection		
8.1. Control parameters			
OIL, MONKEY FARTS* (N/A)			
No additional information available			
Allyl (3-methylbutoxy)acetate (67634-00-8)			
No additional information available			
ALLYL CYCLOHEXYLPROPIONATE (2705-87- No additional information available	ALLYL CYCLOHEXYLPROPIONATE (2705-87-5)		
BENZYL BENZOATE (120-51-4)			
No additional information available			
D-LIMONENE (5989-27-5) No additional information available			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LINALOOL (78-70-6)
No additional information available
ETHYL CAPROATE (123-66-0)
No additional information available
VANILLIN (121-33-5)
No additional information available
ETHYL BUTYRATE (105-54-4)
No additional information available
COUMARIN (91-64-5)
No additional information available
ALLYL HEXANOATE (123-68-2)
No additional information available
ANISIC ALDEHYDE (123-11-5)
No additional information available

8.2. Appropriate engineering controls

: Ensure good ventilation of the work station.

Appropriate engineering controls Environmental exposure controls

: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.



SECTION 9: Physical and chemical	properties	
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Color	: COLORLESS TO YELLOW	
Odor	: CHARACTERISTIC, MATCHING THE RETAINER SAMPLE.	
Odor threshold	: No data available	
pH	: No data available	
Melting point	: Not applicable	
Freezing point	: No data available	
Boiling point	: No data available	
Flash point	: 84 °C	
Relative evaporation rate (butyl acetate=1)	: No data available	
Flammability (solid, gas)	: Not applicable.	
Vapor pressure	: No data available	
Relative vapor density at 20°C	: No data available	
Relative density	: 0.945 (0.935 – 0.955)	
02/14/2024	EN (English US)	4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
9.2. Other information	

Refractive index

: 1.462 (1.452 - 1.472)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.
ATE US (vapors)	15.789 mg/l/4h
Allyl (3-methylbutoxy)acetate (67634-00-8)	
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.5 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
ALLYL CYCLOHEXYLPROPIONATE (2705-87	·-5)
LD50 oral rat	585 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 480 - 714
LD50 dermal rabbit	1600 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 430 - 2770
ATE US (oral)	380 mg/kg body weight
ATE US (dermal)	1600 mg/kg body weight
BENZYL BENZOATE (120-51-4)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bw/day (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)
ATE US (oral)	1160 mg/kg body weight

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

D-LIMONENE (5989-27-5)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Read-across, Dermal, 7 day(s))
LINALOOL (78-70-6)	
ATE US (oral)	2790 mg/kg body weight
VANILLIN (121-33-5)	
LD50 oral rat	3300 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimenta
	value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3300 mg/kg body weight
ATE US (dermal)	2600 mg/kg body weight
ETHYL BUTYRATE (105-54-4)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Remarks on results: other:
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LC50 Inhalation - Rat [ppm]	> 4000 ppm Animal: rat, Guideline: other:, Remarks on results: other:
COUMARIN (91-64-5)	
LD50 oral rat	293 mg/kg body weight Animal: rat, Guideline: other:
LD50 dermal rat	293 mg/kg body weight Animal: rat, Guideline: other:
ATE US (oral)	290 mg/kg body weight
ATE US (dermal)	293 mg/kg body weight
ALLYL HEXANOATE (123-68-2)	
ATE US (oral)	300 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
ANISIC ALDEHYDE (123-11-5)	
LD50 oral rat	3210 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimenta value, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Experimental value, Dermal, 14 day(s))
ATE US (oral)	3210 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified

STOT-single exposure

: Not classified

STOT-repeated exposure

: May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

COUMARIN (91-64-5)	
NOAEL (subchronic,oral,animal/female,90 days)	> 138.3 mg/kg body weight Animal: mouse, Animal sex: female
ANISIC ALDEHYDE (123-11-5)	
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
/iscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
SECTION 12: Ecological informa	tion
2.1. Toxicity	
cology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Allyl (3-methylbutoxy)acetate (67634-00	-8)
LC50 - Fish [1]	≈ 0.768 mg/l Test organisms (species):
ALLYL CYCLOHEXYLPROPIONATE (27	05-87-5)
LC50 - Fish [1]	0.13 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	3.8 mg/l Test organisms (species): Daphnia magna
BENZYL BENZOATE (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
D-LIMONENE (5989-27-5)	
LC50 - Fish [1]	720 μg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	0.307 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi- static system, Fresh water, Experimental value, GLP)
LC50 - Fish [2]	702 μg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
VANILLIN (121-33-5)	
LC50 - Fish [1]	57 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	36.79 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
LC50 - Fish [2]	123 mg/l Test organisms (species): Pimephales promelas
ErC50 algae	120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	5.9 mg/I Test organisms (species): Daphnia magna Duration: '21 d'
ETHYL BUTYRATE (105-54-4)	
LC50 - Fish [1]	≥ 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	116.6 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	28833 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	1483 mg/l Test organisms (species): other: Duration: '28 d'
COUMARIN (91-64-5)	
LC50 - Fish [1]	2.94 mg/l Test organisms (species):
EC50 - Crustacea [1]	8012 mg/l Test organisms (species): Daphnia sp.
LC50 - Fish [2]	1324 mg/l Test organisms (species):
NOEC (chronic)	0.5 mg/l Test organisms (species): Duration: '21 d'
NOEC chronic fish	0.191 mg/l Test organisms (species): Duration: '30 d'

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ANISIC ALDEHYDE (123-11-5)	
LC50 - Fish [1]	148.32 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	82.8 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
ErC50 algae	61 mg/l (DIN 38412-9, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
LOEC (chronic)	1.53 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.71 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

BENZYL BENZOATE (120-51-4)		
Persistence and degradability	Readily biodegradable in water.	
D-LIMONENE (5989-27-5)		
Persistence and degradability	Readily biodegradable in water.	
ThOD	3.29 g O ₂ /g substance	
VANILLIN (121-33-5)		
Persistence and degradability	Readily biodegradable in water.	
ANISIC ALDEHYDE (123-11-5)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

BENZYL BENZOATE (120-51-4)		
BCF - Fish [1]	193.4 l/kg (BCFBAF v3.01, Pisces, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (Experimental value, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
D-LIMONENE (5989-27-5)		
BCF - Fish [1]	864.8 l/kg (BCFBAF v3.01, Pisces, QSAR, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (Experimental value, Equivalent or similar to OECD 117, 37 °C)	
Bioaccumulative potential	Potential for bioaccumulation ($4 \le Log$ Kow ≤ 5).	
VANILLIN (121-33-5)		
Partition coefficient n-octanol/water (Log Pow)	1.17 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

ANISIC ALDEHYDE (123-11-5)

Partition coefficient n-octanol/water (Log Pow)	1.56 (Practical experience/observation, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

BENZYL BENZOATE (120-51-4)	
Surface tension	27 mN/m (210 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Low potential for mobility in soil.
D-LIMONENE (5989-27-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.049 – 3.801 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for mobility in soil.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

VANILLIN (121-33-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.438 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.
ANISIC ALDEHYDE (123-11-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Experimental value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

13.1 Disposal methods Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. SECTION 14: Transport information Department of Transport document description (DOT) In accordance with DOT Transport document description (DOT) In accordance with DOT Class (DOT) : NA1993 Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk Class (DOT) : Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk Class (DOT) : Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk OT Packaging Subk (49 CFR 173.xxx) : 203 DOT Syncbis : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name DOT Syncbis : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for thrasporting a single bulk hazardous material for blasting by carge link motor vehicles (CTWV); and b. The standards for CTWVs capable of transporting multiple hazardous materials for blasting be carge link motor vehicles (CTWV); and b. The standards for CTWVs capable of transporting a single bulk hazardous materials for blasting by carge link motor vehicles (CTWV); and b. The standards for CTWVs capable of transporting and 31NP. Rigd plastics (31HT and 31H2). Composite (31HZ 1 and 31H2).	SECTION 13: Disposal consideration)S
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. SECTION 14: Transport information Department of Transport document description (DOT) : NA1993 Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk, Comb Liq, III UN-No. (DOT) : NA1993 Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk Class (DOT) : Comb Liq - Combustible liquid Packing group (DOT) : III - Minor Danger DOT Packaging Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 172.xxx) : 203 DOT Special Provisions (49 CFR 172.102) : 148 - For domestic ransportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMV/s capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). B3 - Authorized IBCs: Metal (31A, 31B and 31H); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 3		
Department of Transportation (DOT) In accordance with DOT Transport document description (DOT) : NA1993 Combustible liquid, n.o.s. (d-Limonene, Linalcol) - Regulated for Bulk, Comb Liq, III UN-No.(DOT) : NA1993 Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (d-Limonene, Linalcol) - Regulated for Bulk Class (DOT) : Comb Liq - Combustible liquid Packing group (DOT) : III - Minor Danger DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.102) : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). IB3 - Authorized IBCS: Metal (31A, 31B and 31N; Rigid plastics (31H and 31H2); Composite (31H21 and 31H22, 23HN2, 31HD2 and 31H12). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 Additional Requirement: Only liquids with a vapor pressure less than or equal to 110, that at 122; p. or 30 kPa at 55 C (1.3 bara t131 F) are authorized, exce		: Dispose of contents/container in accordance with licensed collector's sorting instructions.
In accordance with DOTTransport document description (DOT): NA1993 Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk, Comb Liq, IIIUN-No.(DOT): Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for BulkProper Shipping Name (DOT): Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for BulkClass (DOT): Comb Liq - Combustible liquidPacking group (DOT): UII - Minor DangerDOT Packaging Non Bulk (49 CFR 173.xxx): 203DOT Packaging Bulk (49 CFR 173.xxx): 241DOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e. a multipuryose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (314, 318 and 31N); Rigid plastics (31H1 and 31H2); Composite (G1M1421 and 31HA2, 31HB2, 31HD2, 31	SECTION 14: Transport information	
Transport document description (DOT)It N1993 Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk, Comb Liq, IIIUN-No.(DOT)It N1993Proper Shipping Name (DOT)It Combustible liquid, n.o.s.Class (DOT)Comb Liq - Combustible liquidPacking group (DOT)III - Minor DangerDOT Packaging Nun Bulk (49 CFR 173.xxx)203DOT Packaging Bulk (49 CFR 173.xxx)It Al - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a technical nameDOT Special Provisions (49 CFR 172.102)148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2; Composite (51H21 and 31H2, 31HB2, 31HD2, a) TIH2; Additional Requirement: Only liquids with a vapor pressure less than or equito 101 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 2 for UN2672). T1 - 15 fra8 Zr4(d)(2) Normal	• • • • •	
Proper Shipping Name (DOT):::Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for BulkClass (DOT):::Combustible liquidPacking group (DOT)::III - Minor DangerDOT Packaging Non Bulk (49 CFR 173.xxx)::2 43DOT Symbols::D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical nameDOT Special Provisions (49 CFR 172.102)::48 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). IB 3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HA2		: NA1993 Combustible liquid, n.o.s. (d-Limonene, Linalool) - Regulated for Bulk, Comb Liq, III
(d-Limonene, Linalool) - Regulated for BulkClass (DOT): Comb Liq - Combustible liquidPacking group (DOT): III - Minor DangerDOT Packaging Non Bulk (49 CFR 173.xxx): 203DOT Packaging Bulk (49 CFR 173.xxx): 241DOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e. a multipurpose bulk trock (MBTT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equiprose bulk term, et as 125 C (1.1 as at 125 F), IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equiprose bulk transmum tegree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (t - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.DOT Packaging Exceptions (49 CFR 173.xxx): 150DOT Quantity Limitations Passenger aircraft/rail: 60 L(49 CFR 173.27): 220 LDOT Vessel Stowage Location: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	UN-No.(DOT)	: NA1993
Class (DOT): Comb Liq - Combustible liquidPacking group (DOT): III - Minor DangerDOT Packaging Non Bulk (49 CFR 173.xxx): 203DOT Packaging Bulk (49 CFR 173.xxx): 241DOT Symbols: D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical nameDOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31H22, 31HB2, 31HD2, and 31N); Rigid plastics (31H1 and 31H2); Composite (171K272). T1 - 1.5 178.274(d)(2) Normal	Proper Shipping Name (DOT)	: Combustible liquid, n.o.s.
Packing group (DOT): III - Minor DangerDOT Packaging Non Bulk (49 CFR 173.xxx): 203DOT Packaging Bulk (49 CFR 173.xxx): 241DOT Symbols: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical nameDOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e. a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31H42, 31HB2, 31HD2, 31HD2, 31HD2, Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27): 200 LDOT Quantity Limitations Cargo aircraft only (49 CFR 175.75): 202 LDOT Vessel Stowage Location: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.		(d-Limonene, Linalool) - Regulated for Bulk
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.102) : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e., a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31H42, 31HB2, 31HB2, 31HD2, a1H22, a1HD2 and 31H); Rigid plastics (21H1 and 31H2); Composite (31H21 and 31H2); Composite (31H21 and 31H2, 23HB2, 31HD2, a1HD2, and 150 C (1.1 bar at 132 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal	Class (DOT)	: Comb Liq - Combustible liquid
DOT Packaging Bulk (49 CFR 173.xxx): 241DOT Symbols: D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical nameDOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMV's capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e. a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HB2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal	Packing group (DOT)	: III - Minor Danger
DOT Symbols:D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical nameDOT Special Provisions (49 CFR 172.102):148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); composite (31H21 and 31H42, 31HB2, 31HB2, 31HD2 and 31H12). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal	DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Special Provisions (49 CFR 172.102): 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMvs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HD2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal	DOT Packaging Bulk (49 CFR 173.xxx)	: 241
 transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). B3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HB2, 31HD2 and 31H2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal	DOT Symbols	
DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49) : 220 L CFR 175.75) : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	· · · · · ·	transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal
(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 220 L CFR 175.75) DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.		
CFR 175.75) DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.		: 60 L
passenger vessel.		: 220 L
Other information : No supplementary information available.	DOT Vessel Stowage Location	
	Other information	: No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Allyl (3-methylbutoxy)acetate (67634-00-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
BENZYL BENZOATE (120-51-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
ETHYL BUTYRATE (105-54-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
COUMARIN (91-64-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
ALLYL HEXANOATE (123-68-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
ANISIC ALDEHYDE (123-11-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations CANADA

Allyl (3-methylbutoxy)acetate (67634-00-8)
Listed on the Canadian DSL (Domestic Substances List)
ALLYL CYCLOHEXYLPROPIONATE (2705-87-5)
Listed on the Canadian DSL (Domestic Substances List)
BENZYL BENZOATE (120-51-4)
Listed on the Canadian DSL (Domestic Substances List)
LINALOOL (78-70-6)
Listed on the Canadian DSL (Domestic Substances List)
ETHYL CAPROATE (123-66-0)
Listed on the Canadian DSL (Domestic Substances List)
VANILLIN (121-33-5)
Listed on the Canadian DSL (Domestic Substances List)
ETHYL BUTYRATE (105-54-4)
Listed on the Canadian DSL (Domestic Substances List)
COUMARIN (91-64-5)
Listed on the Canadian DSL (Domestic Substances List)
ALLYL HEXANOATE (123-68-2)
Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ANISIC ALDEHYDE (123-11-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ALLYL CYCLOHEXYLPROPIONATE (2705-87-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
LINALOOL (78-70-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
ETHYL CAPROATE (123-66-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
VANILLIN (121-33-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

▲ WARNING:
 This product can expose you to furocoumarines (e. g. trioxysalen (inn), 8-methoxypsoralen, 5-methoxypsoralen) except for normal content in natural essences used. in sunprotection and in bronzing products, furocoumarines shall be below
 ▲ WARNING:

This product can expose you to beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
ETHYL CAPROATE(123-66-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
ETHYL BUTYRATE(105-54-4)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date

: 02/14/2024

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

text of H-phrases:	
H226	Flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012) - Lebermuth

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.