

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 11/30/2018 Revision date: 09/18/2024 Supersedes: 09/13/2024

Version: 1.7

## **SECTION 1: Identification**

### 1.1. Identification

Product form : Substance

Product name : FIR NEEDLE SIBERIAN OIL

CAS-No. : 8021-29-2 Product code : 50-6125-01

#### 1.2. Recommended use and restrictions on use

### 1.3. Supplier

The Lebermuth Company 4004 Technology Drive South Bend, IN 46628 - United States T 574-259-7000 - F 574-258-7450 info@lebermuth.com - www.lebermuth.com

### 1.4. Emergency telephone number

Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300

CCN 13010

# SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

### **GHS US classification**

Flammable liquids Category 3 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Skin sensitization, Category 1

Skin sensitization, Category 1
Aspiration hazard Category 1

Flammable liquid and vapor Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction

May be fatal if swallowed and enters airways

## 2.2. GHS Label elements, including precautionary statements

## **GHS US labeling**

Hazard pictograms (GHS US)





GHS02 GHS07

Signal word (GHS US) : Danger

Hazard statements (GHS US) : Flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes skin irritation

May cause an allergic skin reaction Causes serious eye irritation

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center or doctor.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

09/18/2024 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

and easy to do. Continue rinsing.

Specific treatment (see supplemental first aid instruction on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Name	Product identifier	%	GHS US classification
FIR NEEDLE OIL	(CAS-No.) 8021-29-2	100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

# 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin

irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung edema.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : No direct explosion hazard.
Reactivity : Flammable liquid and vapor.

09/18/2024 EN (English US) 2/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid

: Not expected to present a significant hazard under anticipated conditions of normal use.

breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Store always product in container of same material as original container.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### FIR NEEDLE OIL (8021-29-2)

No additional information available

# 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

09/18/2024 EN (English US) 3/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

### Hand protection:

Protective gloves

## Eye protection:

Chemical goggles or safety glasses

## Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment







# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : COLORLESS TO PALE YELLOW LIQUID

Odor : AROMATIC ODOR
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : 43 °C

Relative evaporation rate (butyl acetate=1) : No data available
Flammability : Not applicable.

Vapor pressure : No data available
Relative vapor density at 20°C : No data available
Relative density : 0.897 (0.887 – 0.907)

Solubility : Insoluble.

: No data available Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

# 9.2. Other information

VOC content : 88.6 %

Refractive index : 1.47 (1.462 – 1.477)

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Flammable liquid and vapor.

09/18/2024 EN (English US) 4/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung edema.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

### 12.2. Persistence and degradability

No additional information available

# 12.3. Bioaccumulative potential

No additional information available

# 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

09/18/2024 EN (English US) 5/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sewage disposal recommendations

: Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.

Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.

### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description (DOT) : UN1272 Pine oil (Regulated for Bulk only), 3, III

UN-No.(DOT) : UN1272
Proper Shipping Name (DOT) : Pine oil

(Regulated for Bulk only)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



Marine pollutant : Yes (IMDG only)



: 203

: 242

DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 129

Other information : No supplementary information available.

**Transportation of Dangerous Goods** 

Transport document description (TDG) : UN1272 PINE OIL (Regulated for Bulk only), 3, III

UN-No. (TDG) : UN1272
Proper Shipping Name (TDG) : PINE OIL

09/18/2024 EN (English US) 6/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group (TDG) : III - Minor Danger

Explosive Limit and Limited Quantity Index : 5 L
Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

### Transport by sea

Transport document description (IMDG) : UN 1272 PINE OIL, 3, III, MARINE POLLUTANT (57°C c.c.)

UN-No. (IMDG) : 1272
Proper Shipping Name (IMDG) : PINE OIL

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Marine pollutant : Yes (IMDG only)



### Air transport

Transport document description (IATA) : UN 1272 Pine oil, 3, III

UN-No. (IATA) : 1272
Proper Shipping Name (IATA) : Pine oil

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Low danger

### **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

## FIR NEEDLE OIL (8021-29-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# 15.2. International regulations

# **CANADA**

### FIR NEEDLE OIL (8021-29-2)

Listed on the Canadian DSL (Domestic Substances List)

## **EU-Regulations**

No additional information available

# **National regulations**

No additional information available

### 15.3. US State regulations

**⚠** WARNING:

This product can expose you to beta-myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

# **SECTION 16: Other information**

Revision date : 09/18/2024

09/18/2024 EN (English US) 7/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

ii text of 11 prilades.	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

SDS US (GHS HazCom 2012) - Lebermuth

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

09/18/2024 EN (English US) 8/8