



# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 11/18/2024

Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : OIL, ELECTRIC CHERRY TOM FORD TYPE\*  
Product code : 94-4018-03

#### 1.2. Recommended use and restrictions on use

#### 1.3. Supplier

The Lebermuth Company  
4004 Technology Drive  
South Bend, IN 46628 - United States  
T 574-259-7000 - F 574-258-7450  
[info@lebermuth.com](mailto:info@lebermuth.com) - [www.lebermuth.com](http://www.lebermuth.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300  
CCN 13010

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 4	Combustible liquid
Serious eye damage/eye irritation Category 2A	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Reproductive toxicity Category 2	Suspected of damaging fertility or the unborn child

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



GHS07



GHS08

Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Combustible liquid  
May cause an allergic skin reaction  
Causes serious eye irritation  
Suspected of damaging fertility or the unborn child

Precautionary statements (GHS US) :

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands, forearms and face thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin: Wash with plenty of water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Specific treatment (see supplemental first aid instruction on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use media other than water to extinguish.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone	(CAS-No.) 54464-57-2	1 – 5	Skin Irrit. 2, H315 Skin Sens. 1B, H317
HYDROXYCITRONELLAL	(CAS-No.) 107-75-5	1 – 5	Eye Irrit. 2A, H319 Skin Sens. 1B, H317
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol	(CAS-No.) 63500-71-0	1 – 5	Eye Irrit. 2A, H319
3,7-Dimethyl-1,6-nonadien-3-ol	(CAS-No.) 10339-55-6	1 – 5	Flam. Liq. 4, H227 Eye Irrit. 2A, H319 Skin Sens. 1B, H317
D-LIMONENE	(CAS-No.) 5989-27-5	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304
Diethyl Malonate	(CAS-No.) 105-53-3	1 – 5	Eye Irrit. 2A, H319
LINALOOL	(CAS-No.) 78-70-6	1 – 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317
$\alpha$ -Methyl-1,3-benzodioxole-5-propionaldehyde	(CAS-No.) 1205-17-0	0.1 – 1	Skin Sens. 1B, H317 Repr. 2, H361
CITRAL	(CAS-No.) 5392-40-5	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: No data available.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: No data available.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
-------------	-----------------------

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: No direct explosion hazard.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep cool. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OIL, ELECTRIC CHERRY TOM FORD TYPE\*

No additional information available

#### 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone (54464-57-2)

No additional information available

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>α-Methyl-1,3-benzodioxole-5-propionaldehyde (1205-17-0)</b>	
No additional information available	
<b>HYDROXYCITRONELLAL (107-75-5)</b>	
No additional information available	
<b>2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)</b>	
No additional information available	
<b>3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)</b>	
No additional information available	
<b>Diethyl Malonate (105-53-3)</b>	
No additional information available	
<b>D-LIMONENE (5989-27-5)</b>	
No additional information available	
<b>LINALOOL (78-70-6)</b>	
No additional information available	
<b>CITRAL (5392-40-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Citral
ACGIH OEL TWA	5 ppm (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Body weight eff; URT irr; eye dam. Notations: Skin; DSEN; A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : COLORLESS TO YELLOW  
Odor : CHARACTERISTIC, MATCHING RETAINER SAMPLE  
Odor threshold : No data available  
pH : No data available

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 92 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.9958 (0.9858 – 1.0058)
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

Refractive index	: 1.45645 (1.44645 – 1.46645)
------------------	-------------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### **α-Methyl-1,3-benzodioxole-5-propionaldehyde (1205-17-0)**

ATE US (oral)	3562 mg/kg body weight
---------------	------------------------

#### **3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)**

LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
ATE US (oral)	5000 mg/kg body weight

#### **D-LIMONENE (5989-27-5)**

LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
---------------	---

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

D-LIMONENE (5989-27-5)	
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Read-across, Dermal, 7 day(s))
LINALOOL (78-70-6)	
ATE US (oral)	2790 mg/kg body weight
CITRAL (5392-40-5)	
LD50 oral rat	≈ 6800 mg/kg body weight Animal: rat
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Remarks on results: other:
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

CITRAL (5392-40-5)	
NOAEL (chronic,oral,animal/male,2 years)	60 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)	
NOAEL (dermal,rat/rabbit,90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

CITRAL (5392-40-5)	
LOAEC (inhalation,rat,gas,90 days)	68 ppm Animal: rat, Animal sex: female
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEC (inhalation,rat,gas,90 days)	34 ppm Animal: rat, Animal sex: female
NOAEL (subchronic,oral,animal/male,90 days)	60 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: No data available.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: No data available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)	
LC50 - Fish [1]	24 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	23 mg/l Test organisms (species): Daphnia magna

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

D-LIMONENE (5989-27-5)	
LC50 - Fish [1]	720 µg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 - Crustacea [1]	0.307 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)
LC50 - Fish [2]	702 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
CITRAL (5392-40-5)	
LC50 - Fish [1]	6.78 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	6.8 mg/l Test organisms (species): Daphnia magna

### 12.2. Persistence and degradability

D-LIMONENE (5989-27-5)	
Persistence and degradability	Readily biodegradable in water.
ThOD	3.29 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

D-LIMONENE (5989-27-5)	
BCF - Fish [1]	864.8 l/kg (BCFBAF v3.01, Pisces, QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.38 (Experimental value, Equivalent or similar to OECD 117, 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).

### 12.4. Mobility in soil

D-LIMONENE (5989-27-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.049 – 3.801 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for mobility in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)	: UN1266 Perfumery products (Regulated for Bulk only), Comb Liq, III
UN-No.(DOT)	: UN1266
Proper Shipping Name (DOT)	: Perfumery products (Regulated for Bulk only)
Class (DOT)	: Comb Liq - Combustible liquid
Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.

### Transportation of Dangerous Goods

Not regulated

### Transport by sea

Not regulated

### Air transport

Not regulated

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)

EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.
--------------------------	--

#### Diethyl Malonate (105-53-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone (54464-57-2)

Listed on the Canadian DSL (Domestic Substances List)

#### $\alpha$ -Methyl-1,3-benzodioxole-5-propionaldehyde (1205-17-0)

Listed on the Canadian DSL (Domestic Substances List)

#### HYDROXYCITRONELLAL (107-75-5)

Listed on the Canadian DSL (Domestic Substances List)



# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Diethyl Malonate (105-53-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>LINALOOL (78-70-6)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>CITRAL (5392-40-5)</b>
Listed on the Canadian DSL (Domestic Substances List)


**EU-Regulations**

No additional information available

**National regulations**

<b>1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone (54464-57-2)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
<b>α-Methyl-1,3-benzodioxole-5-propionaldehyde (1205-17-0)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
<b>HYDROXYCITRONELLAL (107-75-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
<b>2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol (63500-71-0)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
<b>3,7-Dimethyl-1,6-nonadien-3-ol (10339-55-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
<b>LINALOOL (78-70-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)
<b>CITRAL (5392-40-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on INSQ (Mexican National Inventory of Chemical Substances)

**15.3. US State regulations**

 **WARNING:**

This product can expose you to methanol - impurity, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

This product can expose you to beta-myrcene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
Diethyl Malonate(105-53-3)	U.S. - New Jersey - Right to Know Hazardous Substance List

**SECTION 16: Other information**

# OIL, ELECTRIC CHERRY TOM FORD TYPE\*

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012) - Lebermuth

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*